

# **SAFETY DATA SHEET**

Version 3.0 Revision Date 09/04/2017

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### 1.1Product identifiers

Product name : Nickel Brand : SAM

CAS-No. : 7440-02-0

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

## 1.3 Details of the supplier of the safety data sheet

Stanford Advanced

Company : Materials

23661 Birtcher Dr. Lake Forest, CA 92630

USA

Telephone : +1 (949) 407-8904Fax : +1 (949) 812-6690

#### 1.4 Emergency telephone number

Emergency Phone # : +1-(949) 407-8904

#### 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

## GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable solids (Category 2), H228 Skin sensitisation (Category 1), H317 Carcinogenicity (Category 2), H351

Specific target organ toxicity - repeated exposure, Inhalation (Category 1), H372

Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Danger

Hazard statement(s)

H228 Flammable solid.

H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure if

inhaled.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and

understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to

extinguish.

P391 Collect spillage. P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Formula : Ni

 Molecular weight
 : 58.69 g/mol

 CAS-No.
 : 7440-02-0

 EC-No.
 : 231-111-4

 Index-No.
 : 028-002-01-4

## **Hazardous components**

Component	Classification	Concentration
Nickel, powder [particle diameter < 1 mm]		
-	Flam. Sol. 2; Skin Sens. 1;	<= 100 %
	Carc. 2; STOT RE 1; Aquatic	
	Acute 1; Aquatic Chronic 1;	
	H228, H317, H351, H372,	
	H410	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

## General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

## In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

## In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment

needed No data available

#### 5. FIREFIGHTING MEASURES

## 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

## 5.2 Special hazards arising from the substance or mixture

No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

## 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal. Contain spillage, pick up with an electrically protected vacuum cleaner or by wetbrushing and transfer to a container for disposal according to local regulations (see section 13).

## 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

## 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Handle and store under inert gas. Keep in a dry place.

Storage class (TRGS 510): Flammable solid hazardous materials

# 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

#### 8. EXPOSURE CONTROLS/PERSONAL

# **PROTECTION 8.1 Control parameters**

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Nickel, powder [particle diameter < 1 mm]	7440-02-0	TWA	1.5 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Dermatitis Pneumoconiosis Not suspected as a human carcinogen		
		TWA	1 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.015 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential Occupational Carcinogen		
		See Appendix A   PEL   0.5 mg/m3   California permissible exposure		California permissible exposure
				limits for chemical contaminants (Title 8, Article 107)

## 8.2Exposure controls

## **Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

## Personal protective equipment

## Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

## Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method:

EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

## **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

## Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a) Appearance Form: powder

Colour: white, silver, metallic

b) Odourc) Odour Thresholdd) pHNo data availableNo data available

e) Melting point/freezing

point

Melting point/range: 1,453 °C (2,647 °F) - lit.

f) Initial boiling point and

boiling range

2,732 °C (4,950 °F) - lit.

g) Flash point Not applicableh) Evaporation rate No data available

Flammability (solid, gas) The substance or mixture is a flammable solid with the category 2.

j) Upper/lower flammability or explosive limits No data available

k) Vapour pressure 1 hPa (1 mmHg) at 1,810 °C (3,290 °F)

I) Vapour density No data available

m) Relative density 8.9 g/cm3 at 25 °C (77 °F)

n) Water solubility insoluble

o) Partition coefficient: n-

octanol/water

No data available

p) Auto-ignition N

temperature

No data available

q) Decomposition temperature

No data available

r) Viscosity No data availables) Explosive properties No data availablet) Oxidizing properties No data available

# 9.2 Other safety information

No data available

## 10. STABILITY AND REACTIVITY

## 10.1 Reactivity

No data available

## 10.2 Chemical stability

Stable under recommended storage conditions.

## 10.3 Possibility of hazardous reactions

No data available

## 10.4 Conditions to avoid

Heat, flames and sparks.

#### 10.5 Incompatible materials

acids, Oxidizing agents, Sulphur compounds, Hydrogen gas, Oxygen, Methanol, organic solvents, Aluminium, Fluorine, Ammonia

# 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Nickel/nickel oxides

Other decomposition products - No data available

In the event of fire: see section 5

#### 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

# **Acute toxicity**

No data available

Inhalation: No data available

Dermal: No data available

No data available

#### Skin corrosion/irritation

No data available

# Serious eye damage/eye irritation

No data available

# Respiratory or skin sensitisation Germ cell mutagenicity

No data available

## Carcinogenicity

This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

Limited evidence of carcinogenicity in animal studies

IARC: 1 - Group 1: Carcinogenic to humans (Nickel, powder [particle diameter < 1 mm])

2B - Group 2B: Possibly carcinogenic to humans (Nickel, powder [particle diameter < 1 mm])

IARC: 1 - Group 1: Carcinogenic to humans (Nickel, powder [particle diameter < 1 mm])

2B - Group 2B: Possibly carcinogenic to humans (Nickel, powder [particle diameter < 1 mm])

NTP: Reasonably anticipated to be a human carcinogen (Nickel, powder [particle diameter <

1 mm])

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as

a carcinogen or potential carcinogen by OSHA.

#### Reproductive toxicity

No data available

No data available

# Specific target organ toxicity - single exposure

No data available

## Specific target organ toxicity - repeated exposure

Inhalation - Causes damage to organs through prolonged or repeated exposure.

# Aspiration hazard

No data available

#### **Additional Information**

RTECS: Not available

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

#### 12. ECOLOGICAL INFORMATION

## 12.1 Toxicity

Toxicity to fish LC50 - Cyprinus carpio (Carp) - 1.3 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 1 mg/l - 48 h

# 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

## 13. DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

#### Product

Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

## Contaminated packaging

Dispose of as unused product.

#### 14. TRANSPORT INFORMATION

DOT (US)

UN number: 3089 Class: 4.1 Packing group: II

Proper shipping name: Metal powders, flammable, n.o.s.

Reportable Quantity (RQ): 100 lbs

Poison Inhalation Hazard: No.

**IMDG** 

UN number: 3089 Class: 4.1 Packing group: II EMS-No: F-G, S-G

Proper shipping name: METAL POWDER, FLAMMABLE, N.O.S. (Nickel, powder [particle diameter < 1 mm])

Marine pollutant:yes

**IATA** 

UN number: 3089 Class: 4.1 Packing group: II

Proper shipping name: Metal powder, flammable, n.o.s.

# 15. REGULATORY INFORMATION

# SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. Revision Date 7440-02-0 2007-07-01

Nickel, powder [particle diameter < 1 mm]

Page 7 of 8

#### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

## **Massachusetts Right To Know Components**

maccachacotto ragnit no ranom componente		
·	CAS-No.	<b>Revision Date</b>
Nickel, powder [particle diameter < 1 mm]	7440-02-0	2007-07-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Nickel, powder [particle diameter < 1 mm]	7440-02-0	2007-07-01
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Nickel, powder [particle diameter < 1 mm]	7440-02-0	2007-07-01

## California Prop. 65 Components

WARNING! This product contains a chemical known to the State of California to cause cancer. CAS-No. Revision Date 2007-09-28

Nickel, powder [particle diameter < 1 mm]

## **16. OTHER INFORMATION**

## Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute Acute aquatic toxicity
Aquatic Chronic Carc. Carcinogenicity
Flam. Sol. Flammable solids
H228 Flammable solid.

H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Skin Sens. Skin sensitisation

## **HMIS Rating**

Health hazard: 2
Chronic Health Hazard: \*
Flammability: 3
Physical Hazard 3

## **NFPA Rating**

Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 3

## **Further information**

This material safety data sheet is offered solely for your information, consideration, and investigation. Stanford Advanced Materials provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein.