



SAFETY DATA SHEET

Version 3.0 Revision Date 09/04/2017

1. PRODUCT AND COMPANY IDENTIFICATION

1.1Product identifiers

Product name : Silica, vitreous

Brand : SAM

CAS-No. : 60676-86-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Stanford Advanced

Company : Materials

23661 Birtcher Dr. Lake Forest, CA 92630

USA

Telephone : +1 (949) 407-8904Fax : +1 (949) 812-6690

1.4 Emergency telephone number

Emergency Phone # : +1 (949) 407-8904

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335 Specific target organ toxicity - repeated exposure, Inhalation (Category 2), Lungs, H373

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word Warning

Hazard statement(s)

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H373 May cause damage to organs (Lungs) through prolonged or repeated

exposure if inhaled.

Precautionary statement(s)

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1Substances

Formula : O₂Si

Molecular weight : 60.08 g/mol CAS-No. : 60676-86-0 EC-No. : 262-373-8

Hazardous components

Component		1	100		Classification : **	Concentration	
Silica, vitreous							
	.00	1,		.**	1,	Eye Irrit. 2A; STOT SE 3; STOT RE 2; H319, H335, H373, H319, H335, H373	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL

PROTECTION 8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis			
and the second	1,		parameters				
Silica, vitreous	60676-86-0	TWA	20.00000Millio	USA. Occupational Exposure Limits			
			n particles per	(OSHA) - Table Z-3 Mineral Dusts			
1,			cubic foot				
	Remarks	Based on impinger samples counted by light-field techniques.					
		mppcf X 35.3 = million particles per cubic meter = particles per c.c					
		See table Z-	See table Z-3				
		TWA	20.000000Millio	USA. Occupational Exposure Limits			
',	: '.	,	n particles per	(OSHA) - Table Z-3 Mineral Dusts			
			cubic foot				
		Based on impinger samples counted by light-field techniques.					
	1, 111	mppcf X 35.3 = million particles per cubic meter = particles per c.c					
		TWA		USA. Occupational Exposure Limits			
			3 / %SiO2	(OSHA) - Table Z-3 Mineral Dusts			
	· .	TWA :	20.000000Millio	USA. Occupational Exposure Limits			
			n particles per	(OSHA) - Table Z-3 Mineral Dusts			
			cubic foot				
		Based on impinger samples counted by light-field techniques.					
		mppcf X 35.3 = million particles per cubic meter = particles per c.c					
'		TWA		USA. Occupational Exposure Limits			
			3 / %SiO2	(OSHA) - Table Z-3 Mineral Dusts			
		TWA	0.050000	USA. NIOSH Recommended			
		,	mg/m3	Exposure Limits			
		Potential Occupational Carcinogen					
		See Append	lix A				

		1	TWA	0.050000 mg/m3	USA. NIOSH Recommended Exposure Limits		
1.	;		Potential Occupational Carcinogen See Appendix A				
			TWA	6.000000 mg/m3	USA. NIOSH Recommended Exposure Limits		
	111	٠, ٠,	TWA	6.000000 mg/m3	USA. NIOSH Recommended Exposure Limits		
			TWA	20Million particles per cubic foot	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts		
	, , ,		Based on impinger samples counted by light-field techniques. mppcf X 35.3 = million particles per cubic meter = particles per c.c				
1.	;		TWA	80mg/m3 / %SiO2	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts		
			TWA	0.05 mg/m3	USA. NIOSH Recommended Exposure Limits		
4.	111	1	Potential Occupational Carcinogen See Appendix A				
			TWA	6 mg/m3	USA. NIOSH Recommended Exposure Limits		
	.**	1,	PEL	0.1 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		

8.2Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm Break through time: 480 min

Material tested: Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

For nuisance exposures use type P95 (US) or type P1 (EU EN 143) particle respirator. For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a) Appearance Form: solidb) Odour No data availablec) Odour Threshold No data available

d) pH No data available

e) Melting point/freezing Melting point/range: 1,610 °C (2,930 °F) - lit. point

f) Initial boiling point and No data available boiling range

g) Flash point Not applicableh) Evaporation rate No data availablei) Flammability (solid, gas) No data available

j) Upper/lower No data available flammability or explosive limits

k) Vapour pressurel) Vapour densityNo data availableNo data available

m) Relative density 2.6 g/cm3 at 25 °C (77 °F)

 n) Water solubility No data available
 o) Partition coefficient: noctanol/water

No data available

p) Auto-ignition No data available temperature

q) Decomposition temperature
 r) Viscosity
 No data available
 No data available
 No data available

No data available

9.2 Other safety information
No data available

Oxidizing properties

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

Other decomposition products - No data available

Hazardous decomposition products formed under fire conditions. - silicon oxides

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Carcinogenicity - Rat - Implant

Tumorigenic:Equivocal tumorigenic agent by RTECS criteria. Gastrointestinal:Tumors. Tumorigenic:Tumors at site or application.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure. - Lungs

Aspiration hazard

No data available

Additional Information

RTECS: VV7328000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

CAS-No.

Revision Date

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

Silica, vitreous	·:	· · .	: "	·:	10	60676-86-0	1993-04-24
Pennsylvania Righ	t To Kı	now Comp	onents				
Silica, vitreous	1,			:,		CAS-No. 60676-86-0	Revision Date 1993-04-24
New Jersey Right	Го Кпо	w Compo	nents				
Silica, vitreous		٠.,	:		٠.,	CAS-No. 60676-86-0	Revision Date 1993-04-24

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eye Irrit. Eye irritation

H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

HMIS Rating

Health hazard: 2
Chronic Health Hazard: *
Flammability: 0
Physical Hazard 0

NFPA Rating

Health hazard: 2
Fire Hazard: 0
Reactivity Hazard: 0

Further information

This material safety data sheet is offered solely for your information, consideration, and investigation. Stanford Advanced Materials provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein.